



690 V			1000 V on a supply, 690 V on c supply			
40 A	50 A	65 A	80 A	95 A	115 A	150 A
60 A	80 A	80 A	125 A		200 A	
11 kW	15 kW	18.5 kW	22 kW	25 kW	30 kW	40 kW
18.5 kW	22 kW	30 kW	37 kW	45 kW	55 kW	75 kW
22 kW	25 kW	30 kW	45 kW	45 kW	59 kW	80 kW
22 kW	30 kW	37 kW	55 kW	55 kW	75 kW	90 kW
30 kW	33 kW	37 kW	45 kW	45 kW	80 kW	100 kW
–	–	–	45 kW	45 kW	75 kW	90 kW
LC1-D40A	LC1-D50A	LC1-D65A	LC1-D80	LC1-D95	LC1-D115	LC1-D150
LC2-D40A	LC2-D50A	LC2-D65A	LC2-D80	LC2-D95	LC2-D115	LC2-D150

Mounting accessories for 3-pole reversing contactors

2 identical contactors with screw clamp terminals or connectors, horizontally mounted

Mechanical interlock	Set of connections	Mechanical interlock
with an electrical interlocking kit for the contactors LC1-D09...D38	LAD-9R1V	included
with integral electrical interlocking LC1-D80 and D95 (a) LC1-D80 and D95 (c) LC1-D115 and D150	LA9-D8069 LA9-D8069 LA9-D11569	LA9-D4002 LA9-D8002 LA9-D11502
without electrical interlocking LC1-D09...D38 LC1-D40A...D65A LC1-D80 and D95 (a) LC1-D80 and D95 (c)	LA9-9R1 LAD-9R3 LA9-D8069 LA9-D8069	included included LA9-D50978 LA9-D80978



Mechanical latch blocks

Clip-on front mounting, manual or electrical unlatching control

For use on contactor	Reference	Standard control circuit voltages
LC1-D09...D65A a or c , LC1-DT20...DT80 a or c	LAD-6K10•	B E F M Q
LC1-D80...D150 3P a , LC1-D80 and D115 3P a , LC1-D115 4P c	LA6-DK20•	B E F M Q