



CLASSIFICATION		REV, PREVENTING RELAY
MODEL		APR-3
DIMENSIONS		50H × 40W × 58D
MOUNING & SOCKET	SURFACE(-N)	PF083A(E) PF085A
	FLUSH(-Y)	P3G-08 US-08
FUNCTIONS		Protecting threepphase induction motor reverse relay 220V sourece with surge absorber and highn voltage protecting
RATED VOLTAGE		AC(V):220,240,380,415,440, 50/60Hz
INDICATOR OPERATING		---
CONTACT OUTPUT	MODEL	APR-3
	TIME LIMIT	10A
LIFE	MECHANICAL	5×10^6 times
	ELECTRICAL	10^5 times
SETTING ERROR		---
RESET TIME		---
CONSUMED POWER		2VA
AMBIENT TEMPERATURE		-10°C~+55°C
AMBIENT HUMINITY		45~85%RH
WEIGHT		90
CONNECTION DIAGRAMS & TIMING CHART		35A



CLASSIFICATION		REV, PREVENTING RELAY
MODEL		JVM-1
DIMENSIONS		61H × 49W × 70D
MOUNING & SOCKET	SURFACE(-N)	PS-08 PF083A(E)
	FLUSH(-Y)	
FUNCTIONS		Protecting threephase induction motor reverse relay 220V sourcee with surge absorber and highn voltage protecting
RATED VOLTAGE		NORMAL Operating
INDICATOR OPERATING		AC(V):220,240,380,415,440, 50/60Hz
CONTACT OUTPUT	MODEL	JVM-1
	TIME LIMIT	10A
LIFE	MECHANICAL	5×10^6 times
	ELECTRICAL	10^5 times
SETTING ERROR		---
RESET TIME		---
CONSUMED POWER		2VA
AMBIENT TEMPERATURE		-10°C~+55°C
AMBIENT HUMINITY		45~85%RH
WEIGHT		90
CONNECTION DIAGRAMS & TIMING CHART		35F