




### Auxiliary contact blocks

instantaneous, screw clamp connections

	■ for LC1, LP1-K, LP4			■ for LC1, LP1-K				
Composition	2N/O	- 2N/C	1N/O 1N/C	4N/O	3N/O 1N/C	2N/C 2N/C	1N/O 3N/C	- 4N/C
Reference	LA1-KN20	LA1-KN02	LA1-KN11	LA1-KN40	LA1-KN31	LA1-KN22	LA1-KN13	LA1-KN04
<b>electronic time delay</b>								
Relay outputs, with common point changeover contact, a or c 24...48, 2 A maximum								
Control voltage 0.85...1.1 Uc								
Maximum switching capacity 250 VA or 150 W								
Operating temperature -10...+ 60°C								
Reset time: 1.5 s during the time delay period, 0.5 s after time delay period								
Type	On-delay							
Timing range	1...30 s							
Composition	1							
Voltage	a or c 24...48 V				a 110...240			
Reference	LA2-KT2E				LA2-KT2U			

5



### Suppressor modules

For LC1, LP1-K

Type	Varistor (a and c )				Diode (c ) + Zener		RC (a )
Voltage	12...24 V	32...48 V	50...129 V	130...250 V	12...24 V	32...48 V	220...250 V
Reference	LA4-KE1B	LA4-KE1E	LA4-KE1FC	LA4-KE1UG	LA4-KC1B	LA4-KC1E	LA4-KA1U