










# Pushbuttons, switches and pilot lights Ø 22 with metal bezel

XB4










## Pilot lights





<b>Type of head</b>		<b>Circular bezel</b>						
<b>Degree of protection</b>		<b>Smooth lens cap</b>						
<b>Mounting (mm)</b>	panel cut-out	IP 66 / Nema 4X, 13 / Class I						
	mounting centres	Ø 22.5 (22.4 <sup>+0.4</sup> <sub>0</sub> recommended)						
<b>Depth</b>	below head	30 (horizontal) x 40 (vertical)						
<b>Connection (1)</b>		43						
<b>Light source</b>		Screw clamp terminals			Integral LED			Direct supply for BA 9s bulb (not included)
	<b>Products</b>	<b>Complete</b>			<b>Complete</b>	<b>For user assembly</b>		
								
<b>Supply voltage</b>		24 V AC/DC	48...120 V AC	230...240 V AC	250 V max., 2.4 W max.			
<b>References</b>	white 	<b>XB4 BVB1</b>	<b>XB4 BVG1</b>	<b>XB4 BVM1</b>	<b>XB4 BV61</b>	ZB4 BV6	ZB4 BV01	
	green 	<b>XB4 BVB3</b>	<b>XB4 BVG3</b>	<b>XB4 BVM3</b>	<b>XB4 BV63</b>	ZB4 BV6	ZB4 BV03	
	red 	<b>XB4 BVB4</b>	<b>XB4 BVG4</b>	<b>XB4 BVM4</b>	<b>XB4 BV64</b>	ZB4 BV6	ZB4 BV04	
	yellow 	<b>XB4 BVB5</b>	<b>XB4 BVG5</b>	<b>XB4 BVM5</b>	<b>XB4 BV65</b>	ZB4 BV6	ZB4 BV05	
	blue 	<b>XB4 BVB6</b>	<b>XB4 BVG6</b>	<b>XB4 BVM6</b>	–	–	–	



## Illuminated pushbuttons and selector switches

<b>Type</b>	Flush push, spring return, illuminated pushbuttons						
<b>Light source</b>		Integral LED			Direct supply for BA 9s bulb (not included)		
	<b>Products</b>	<b>Complete</b>			<b>Complete</b>	<b>For user assembly</b>	
							
<b>Supply voltage</b>		24 V AC/DC	48...120 V AC	230...240 V AC	250 V max., 2.4 W max.		
<b>References</b>	white  N/C + N/O	<b>XB4 BW31B5</b>	<b>XB4 BW31G5</b>	<b>XB4 BW31M5</b>	<b>XB4 BW3165</b>	ZB4 BW065	ZB4 BW31
	green  N/C + N/O	<b>XB4 BW33B5</b>	<b>XB4 BW33G5</b>	<b>XB4 BW33M5</b>	<b>XB4 BW3365</b>	ZB4 BW065	ZB4 BW33
	red  N/C + N/O	<b>XB4 BW34B5</b>	<b>XB4 BW34G5</b>	<b>XB4 BW34M5</b>	<b>XB4 BW3465</b>	ZB4 BW065	ZB4 BW34
	orange  N/C + N/O	<b>XB4 BW35B5</b>	<b>XB4 BW35G5</b>	<b>XB4 BW35M5</b>	<b>XB4 BW3565</b>	ZB4 BW065	ZB4 BW35
	blue  N/C + N/O	<b>XB4 BW36B5</b>	<b>XB4 BW36G5</b>	<b>XB4 BW36M5</b>	–	–	–



<b>Type</b>	Double-headed pushbuttons with LED pilot light (1 flush green push, 1 projecting red push)			Illuminated selector switches (2 position stay put)			
<b>Degree of protection</b>	IP 66 - IP 69K			IP 66			
<b>Light source</b>	Integral LED			Integral LED			
	<b>Products</b>	<b>Complete</b>			<b>Complete</b>		
<b>Supply voltage</b>		24 V AC/DC	48...120 V AC	230...240 V AC	24 V AC/DC	48...120 V AC	230...240 V AC
<b>References</b>	green  N/C + N/O	–	–	–	<b>XB4 BK123B5</b>	<b>XB4 BK123G5</b>	<b>XB4 BK123M5</b>
	red  N/C + N/O	–	–	–	<b>XB4 BK124B5</b>	<b>XB4 BK124G5</b>	<b>XB4 BK124M5</b>
	orange  N/C + N/O	–	–	–	<b>XB4 BK125B5</b>	<b>XB4 BK125G5</b>	<b>XB4 BK125M5</b>
	White  N/C + N/O	<b>XB4 BW73731B5</b>	<b>XB4 BW73731G5</b>	<b>XB4 BW73731M5</b>	–	–	–

(1) Alternative connections: plug-in connector, Faston connectors (6.35 and 2 x 2.8), spring clamp terminal.