



Contact type			instantaneous, connection by screw terminals	
Block mounting			Front mounting	Side mounting
References	Contact	1 N/O	LADN10	–
		1 N/C	LADN01	–
		1 N/O + 1 N/C	LADN11	LAD8N11
		2 N/O	LADN20	LAD8N20
		2 N/C	LADN02	LAD8N02
		2 N/O + 2 N/C	LADN22	–
		1 N/O + 3 N/C	LADN13	–
		3 N/O + 1 N/C	LADN31	–
		4 N/O	LADN40	–
		4 N/C	LADN04	–



Contact type			Time delay, connection by screw terminals		
Block mounting			Front mounting		
Temporisation			0.1...3 s	0.1...30 s	10...180 s
References	On-delay		LADT0	LADT2	LADT4
		Off-delay	LADR0	LADR2	LADR4

Maximum number of auxiliary contacts that can be fitted

Type	Number of poles and size		Instantaneous						Time delay
			Side mounting			Front mounting			Front mounting
			on left side	on right side		1 contact	2 contacts	4 contacts	
AC	3P	LC1D09...D38	1	–	and	–	1	or 1	or 1
		LC1D40A...D65A	1	or 1	and	–	1	or 1	or 1
		LC1D80...95 (50/60 Hz)	1	1	or	2	and 1	or 1	or 1
		LC1D80...95 (50 or 60 Hz)	1	1	and	2	and 1	or 1	or 1
		LC1D115 and D150	1	–	and	–	1	or 1	or 1
	4P	LC1DT20...DT40	1	–	and	–	1	or 1	or 1
LC1DT60A...D80A		1	or 1	and	–	1	or 1	or 1	
LC1D115		1	1	and	1	or 1	or 1	or 1	
DC	3P	LC1D09...D38	–	–	and	–	1	or 1	or 1
		LC1D40A...D65A	1	or 1	and	–	1	or 1	or 1
		LC1D80 and 95	–	–	and	1	or 1	or 1	or 1
		LC1D115 and D150	1	–	and	–	1	or 1	or 1
	4P	LC1DT20...DT40	–	–	and	–	1	or 1	or 1
		LC1DT60A...D80A	–	–	and	–	1	or 1	or 1
		LC1D115	1	1	and	–	and 1	or 1	or 1
DC low consumption	3P	LC1D09...D38	–	–	and	–	1	–	–
	4P	LC1DT20...DT40	–	–	and	–	1	–	–